

DasPell NEXT

15 - 30 kW

5klasa
PN-EN 303-5:2012

ECO design
Rozp. UE 2015/1188

A+



Unit configuration

Standard configuration: Flue gas discharge by exhaust tank on the right side of the boiler. Flue gas discharge by exhaust fan in 5 positions from horizontal at angle: 0°, 45°, 90°, 135°, 180°.



5-year warranty on the tightness of the exchanger.



High thermal efficiency >90% thanks to autoregulation of the combustion process and effective heat reception



Compact design ensuring minimum boiler dimensions.



Vertical burner with automatic cleaning, equipped with a igniter, photoelement, thermocouple.



A vertical tubular heat exchanger with an automatic cleaning system.



An exhaust fan, aerating the burner, stabilizing the operation of the boiler and improving the chimney draft.



Turbulators supporting heat exchange.



The boiler is adapted for operation in closed system, in accordance with current regulations.



The **HT-tronic 900 Touch** weather controller with a touch color display. It controls the operation of 4 pumps and a mixing valve. Works with a remote control panel, thermostats and an internet module. Equipped with an autoregulation the **HT-Logic III**.



HT-Logic III autoregulation is individually programmed for each boiler, it automatically selects the operating parameters and modulates the burner power depending on the boiler temperature, which **reduces the amount of fuel consumed**. Works with the Lambda oxygen probe in the **iPell®** standard - optimization of the combustion process **HT-tronic OPS Lambda**.



The boiler is equipped with a **hydraulic module** consisting of: return protection pump, DHW pump, mixing valve pump, mixing valve with an actuator and a **safety group** consisting of a diaphragm vessel, safety valve and pressure gauge.



The boiler is protected by a return protection pump with a return temperature sensor.



Flue gas exhaust in five positions from the horizontal, at an angle of: 0°, 45°, 90°, 135°, 180°.

iPell® - optimisation of the combustion process - HT-tronic OPS Lambda

Control

HT-tronic® 900 Touch

HT-tronic OPS Lambda Combustion process optimizer with Lambda probe - basic equipment

Expanding modules for automation

HT-tronic M-Z2 Valve module

HT-tronic M-BC Module of buffer and circulation

HT-tronic Rooms Remote control panel with room thermostat (Wired)

HT-tronic Rooms Touch Remote control panel with room thermostat (Touchscreen, Wired)

HT-tronic Rooms Wireless Remote control panel with room thermostat (Wireless data transmission)

HT-tronic Rooms Touch Wireless Remote control panel with room thermostat (Touchscreen, Wireless data transmission)

HT-tronic Connect Web module - access by web browser or mobile application

HT-tronic Climate Senso Wireless sensor for HT-tronic Rooms Touch V2, measurement of temp., air humidity and atmospheric pressure

HT-tronic Temperature Senso Wireless sensor for HT-tronic Rooms Touch V2, measurement of temperature

Additional equipment / Execution option

Chimney connections - 120 Ø - page 31

The automatic ash removal system

HT SepMag | Dirt separator with magnetizer -1". Expenditure 2.8 m³/h for a pressure drop of 6 kPa

Basic dimensions and specifications

	kW	15	20	25	30
Rated power	kW	15	20	25	30
Power range	kW	4,5 - 15	6 - 20	7,5 - 25	9 - 30
Min. chimney draft	Pa	10	12	14	16
Max. work temperature	°C	85	85	85	85
Water capacity	l	75	81	81	119
Maximum operating pressure	Bar	2	2	2	2
Installation connection	"	GZ 1	GZ 1	GZ 1	GZ 1
Chimney connection (inner diameter)	mm	120	120	120	120
Boiler mass	kg	345	405	405	451
Tank volume	dm³	240	240	240	240
Width of the set	cm	85	90	90	95
Boiler width	cm	45	45	45	45
Body depth with a flue gas exhaust	cm	98	98	98	98
Body height	cm	144	144	144	144
Power spigot height	cm	122,5	122,5	122,5	122,5
Height to chimney mid.	cm	120	120	120	120
Return spigot height	cm	34,5	34,5	34,5	34,5

Fuel



pellet (6 - 8 mm) A1 class according to: EN 14961-2:2011 or DIN Plus

Catalog card

