

# COMPEX S-6.2

(21.145)

Voltage	(V)	400	Filter surface	(m <sup>2</sup> )	6,2
Motor	(kW)	4	No. of filter elements	(pc)	30
Ampere	(A)	8,5	Filter material	Dust classification "M"	
Rated frequency	(Hz)	50	Filter cleaning	Automatic Jet	
Fuse	(A)	20	Weight	(kg)	ca. 415
Max. neg. pressure	(Pa)	2.900	Intake	(mm)	2 x 160
Max. airflow	(m <sup>3</sup> /h)	3.250	Dust collection bin	(Liter)	2 x 90
Comp. air connection	(inch)	¼"	Dimensions (l x w x h)	(mm)	1.264 x 804 x 2.220



## ESTA PLUS

### Application range:

Continous duty dust extraction on single and multiple workstations  
Dental labs, plastics industry and shoe industry

### Your benefits at a glance

Specifically designed for rubber, leather and plastic  
High extraction performance  
Cleanable long life cartridge filters  
Low operation costs  
Can be used in different locations as a mobile or stationary unit

### Characteristics:

Pulse-jet filter cleaning system  
Cleanable long life cartridge filter rated for dust classification "M"

Special design with different filter materials, air vent,  
patented fire control device  
Special paintings available

Insertable disposal container in the drawer

State of the art: 21145-51-00 Subject to change without notice! For remaining questions please do not hesitate to contact us.